

PAC EL112 CST


DE'LONGHI COMFORT

AIR-TO-AIR PORTABLE CONDITIONERS

- Maximum cooling capacity
- Low Energy Consumption
- CST Cool Surround Technology
- Eco Real Feel Technology
- Eco-friendly gas
- Silent
- Bluetooth tech
- Louver
- Frontal display

11.000 Btu/h* - 2,9 kW
 Class A+
 Comfort Sensing You
 Up to 30% Energy savings***
 R290


Constant CST temp/hum tracking
 Better air distribution
 Easy to read



2,9 kW



- Fan function
- Dehumidifying function
- LED control panel with Comfort Light Indicator
- Exclusive condensate recirculation system
- 3 fan speed to select the maximum power or the minimum noise
- Soft touch control panel
- Remote control
- 24 h electronic timer and thermostat
- Handles and castors for easy transportation



COMFORT LIGHT INDICATOR / WIDE DISPLAY

Easy understanding of comfort level thanks to the CLI Comfort Light Indicator: orange "seeking for comfort", green "good" Blu "perfect comfort".

SILENT TECHNOLOGY

The silence of power, up to 50% more silent*
 (Tested in our labs by comparing the max fan speed vs min fan speed)

700 TIMES ECO-FRIENDLY

Pinguino PAC EL98 ECOREALFEEL uses the refrigerant gas R290, which is up to 696 times more environmentally friendly than traditional gases****

ECO REAL FEEL TECHNOLOGY

Comfort is the result of correct matching between temperature and humidity. ECO REAL FEEL tracks and acts on both to automatically reach and maintain your desired comfort, at the same time saving up to 30%*** on energy consumption.

CST COMFORT SENSING YOU

Bring the Remote Sensing Unit with you, it will track humidity and temperature around you, making sure you'll always enjoy your desired comfort.

TECHNICAL DATA

Maximum cooling capacity	BTU/h* – Kw**	11.000 – 2,9
Energy Efficiency Ratio (EER)	(W/W)	3,1
For rooms up to	m ³	110
Refrigerant gas		R290
Energy Efficiency Class		A+
Rated voltage – frequency	V~Hz	220-240~50
Input power**	W	950
Standby consumption	W	0,9
Maximum sound power level	dB(A)	63
Noise pressure level (min-max)	dB(A)	47-50
Air flow(min-med-max)	m ³ /h	250-310-350
Max dehumidifying (dehum. mode)	l/24h	41
Dimensions (hxlxp)	mm	750x450x410
Weight	Kg	33

* 35°C/80% R.H.

** 35°C/40% R.H. (EN14511)

***Internal test, initial condition 30° C and 40%RH

****696 times compared to the impact of Global Warming of R410 - F-Gas Reg. 517/2014.

***** Tested in our laboratory by comparing the maximum sound level using max. fan speed vs sound level with min. fan speed



Better Everyday