
N 70 B15CR32N1B SINGLE OVEN STAINLESS STEEL







## Included accessories

 $2 \times combination grid, 1 \times universal pan$ 

## Optional accessories

Z18C60X0 Cookbook



- $\sqrt{\rm CircoTherm^{\odot}}$  the unique hot air-system for simultaneous baking and roasting on up to 3 levels
- $\sqrt{}$  EcoClean the self-cleaning catalytic coating on the inside top and sides of the oven makes oven cleaning easier.
- $\sqrt[N]{}$  BottomClean the special cleaning programme for the oven floor.
- $\sqrt{\,}$  Shift Control fast navigation through menus and simple operation with the TFT display.
- √ Hinged door

### Features

## Technical Data

Color / Material Front : Stainless steel

Construction type: Built-in

Integrated Cleaning system : Catalytic all sides, Hydrolytic

Required niche size for installation (HxWxD) :  $585-595 \times 560-568 \times 10^{-2}$ 

550

Dimensions of the product (mm) :  $595 \times 596 \times 548$ 

Dimensions of the packed product (HxWxD) (mm): 670 x 680 x 670

Control Panel Material : Stainless steel

Door Material : Glass Net weight (kg) : 35.9

Usable volume of cavity (I): 71

Cooking method:, Bottom heat, Bread Baking Setting, Conventional heat, Dough proving setting, Full width grill, Half width grill, Hot Air, Hot Air-Eco, Hot air grilling, low temperature cooking, Pizza setting

First cavity material : Enamelled Temperature control : electronic Number of interior lights : 1 Approval certificates : CE, VDE

Length of electrical supply cord (cm): 120

EAN code: 4242004197256 Number of cavities (2010/30/EC): 1 Energy efficiency class (2010/30/EC): A+

Energy consumption per cycle conventional (2010/30/EC): 0.87 Energy consumption per cycle forced air convection (2010/30/EC):

0.69

Energy efficiency index (2010/30/EC) : 81.2 Electrical connection rating (W) : 2990

Current (A): 13 Voltage (V): 220-240 Frequency (Hz): 50; 60 Plug type: no plug



# N 70 B15CR32N1B SINGLE OVEN STAINLESS STEEL

#### Features

## Design

- 2.5" TFT colour display
- Illuminated Shift Control
- Drop down door

#### **Features**

- Temperature proposal Actual temperature display Heating up indicator Sabbath setting
- Control panel lock
   Automatic safety switch off
   Residual heat indicator
   Start button
   Door contact switch
- Interior halogen light
- Triple glazed door
- Cavity inner surface: Enamel anthracite

## Cleaning

- EcoClean Direct : ceiling, side liners, back panel
- EcoClean programme, Base Clean programme
- Full glass inner door

## Programmes/functions

- Oven with 12 heating methods: CircoTherm®, CircoTherm® Eco, Top/bottom heat, Conventional heat eco, Hot air grilling, Full surface grill, Centre surface grill, CircoTherm® intensive, Bread baking, Bottom heat, Low temperature cooking, Dough proving
- Rapid heat
- Cooling fan
- Info button

## Standard accessories


• 2 x combination grid, 1 x universal pan

# Technical information


- Energy efficiency rating (acc. EU Nr. 65/2014): A+ Energy consumption per cycle in fan-forced convection mode: 0.69 kwh
- Number of cavities: 1 Heat source: electrical Cavity volume: 71 litre
- Temperature range 40 °C 275 °C
- Length of mains cable: 120 cm
- Total connected load electric: 2.99 KW
- $\bullet$  Appliance dimension (hxwxd): 595 mm x 596 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual


# Dimensioned drawings

Installation with a hob.



measurements in mm





If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm