N 30, Built-in oven, 60 x 60 cm, Stainless steel B3CCCOANOB



Built-in Slide&Hide® oven with fixed handle - unrestricted access to the oven interior thanks to the fully retracting oven door

- $\sqrt{\mbox{ Slide\&Hide}^{\mbox{\scriptsize @}}}$ with fixed handle the fully retracting oven door.
- $\sqrt{\rm CircoTherm^{\odot}}$ our smart hot-air solution for simultaneous baking and roasting on up to three levels
- $\sqrt{\mbox{ LED-Display}}$ simple, straightforward for clear reading







Optional accessories

Z11AB15A0 Baking tray, non-stick ceramic coated

Z11CB10E0 Baking tray, grey enamelled

Z11CR10X0 Baking and roasting grid (standard)

Z11GT10X3 Glass roasting dish, 5,4l

Z11GU20X0 Glasspan

Z11TF36X0 3 level telescopic rails, full ext

Z11TI15X0 Cliprails

Z12CQ10A0 Grill tray, anthracite enamelled

Z1913X0 Baking Stone Z19DD10X0 Steam set for ovens

Features

Technical Data

Color / Material Front : Stainless steel Construction type : Built-in Integrated Cleaning system : No

Required niche size for installation (HxWxD) : $585-595 \times 560-568 \times 10^{-2}$

550

Dimensions: 595 x 594 x 548

Dimensions of the packed product (HxWxD) (mm) : $660 \times 690 \times 660$

Control Panel Material : Stainless steel

Door Material : Glass Net weight (kg) : 35.174 Usable volume of cavity (l) : 71

Cooking method: Conventional heat, Full width grill, Hot Air, Hotair

gentle, Hot air grilling
First cavity material : Other
Temperature control : mechanical
Number of interior lights : 1
Approval certificates : CE, VDE

Length of electrical supply cord (cm): 120

EAN code: 4242004248705 Number of cavities (2010/30/EC): 1 Energy efficiency rating: A

Energy consumption per cycle conventional (2010/30/EC) : 1.04 Energy consumption per cycle forced air convection (2010/30/EC) :

0.81

Energy efficiency index (2010/30/EC): 95.3

Connection rating (W): 2990

Current (A): 13 Voltage (V): 220-240 Frequency (Hz): 50; 60 Plug type: no plug





Features

Design

- LED Display (Red)
- Elongated designed dials,Retractable control dials,Bevelled oval controls
- Slide&Hide® with fixed handle
- Enamel grey
- Bar handle
- 4 shelf positions

Features

- automatic start
- Control panel lock
- Interior halogen light

Cleaning

• Full glass inner door

Programmes/functions

- Ovenwith5 main functionsheating methods:CircoTherm®,Top/bottom heat,Circo-roasting,Full surface grill,CircoTherm® gentle
- Cooling fan
- Temperature range50 °C-275 °C

Accessories

• 2 x combination grid, 1 x universal pan

Performance/technical information

- Cavity volume:71 litre
- Energy efficiency rating (acc. EU Nr. 65/2014):A
 Energy consumption per cycle in conventional mode:1.04 kWh
 Energy consumption per cycle in fan-forced convection mode:0.81 kWh


Number of cavities: Main cavity Heat source: electrical Cavity volume:71 litre


- Total connected load electric: 2.99 KW
- 120 cmCable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd):595 mmx594 mmx548 mm
- Niche dimension (hxwxd):585 mm-595 mmx560 mm-568 mmx550 mm
- \bullet Please refer to the dimensions provided in the installation manual





COOKING PASSION SINCE 1877

Dimensioned drawings









If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm