

eiQ-CRFC12K Technical Specification

Internal Unit			
Capacity	Cooling Capacity	Btu/h	13680-12000-4800
		kW	4.0-3.2-1.4
	Heating Capacity	Btu/h	15340-13000-4550
		kW	4.5-4.0-1.3
Electrical	Power Supply	V~,Hz,Ph	220-240, 50, 1
Performance	SEER	W/W	6.1
	Energy Rate	Cooling	A++
	SCOP	W/W	4.0
	Energy Rate	Heating	A+
	Tol	°C	-15.0
	Air Flow Volume	m³/h	683/530/510
	Indoor Sound Power Noise Level dB(A)	dB(A)	58
	Noise Level dB(A)	Hi/Med/Low	42 / 38 / 34
Dimension, Weight &	Net Dimension (mm)	Body (WxHxD)	570x260x570
		Panel (WxHxD)	647x50x647
	Net Weight (kg)	Body	16
		Panel	3
	Packing Dimension (mm)	Body (WxHxD)	655x290x655
		Panel (WxHxD)	705x113x705
	Gross Weight (kg)	Body	20
		Panel	5
Piping Sizes	Piping Size (mm)	Liquid	Ø 6.35(1/4")
		Gas	Ø 9.52(3/8")
		Drainage	ODØ 25

External Unit			
Capacity	Cooling Capacity	Btu/h	12000
		kW	3.2
	Heating Capacity	Btu/h	13000
		kW	4
Electrical	Power Supply	V~,Hz,Ph	220-240, 50, 1
	Air Flow Volume	m³/h	2500
	Noise Level	dB(A)	48
Dimension & Weight	Net Dimension (mm)	WxHxD	760x590x285
	Net Weight	kg	30
	Packing Dim (mm)	WxHxD	887x645x355
	Gross Weight	kg	35
Piping Size	Liquid Size	mm	Ø 6.35(1/4")
	Gas Size	mm	Ø 9.52(3/8")
	Max pipe Length	m	15
	Max height difference	m	8