

Model		eiq-SSRFC24k	
Power supply		V,Hz,Ph	220~240,50,1
Max. input consumption		W	2950
Max. input current		A	14.0
Compressor	Model		ATF235D22UMT
	Type		ROTARY
	Brand		GMCC
	Capacity	Btu/h	24345
	Input	W	1970
	Rated current(RLA)	A	6.95
	Refrigerant oil	ml	POE(VG74)/670
Outdoor fan motor	Model		ZKFN-50-8-2
	Old Model		- -
	Qty		1
	Input	W	115
	Capacitor	μF	/
	Speed(Hi)	r/min	760
Outdoor coil	Number of rows		2
	Tube pitch(a)* row pitch(b)	mm	25.4x22
	Fin spacing	mm	1.4
	Fin type		Hydrophilic aluminium
	Tube outside dia.and type	mm	Φ9.52,innergroove tube
	Coil length * height * width	mm	730x660x44
	Number of circuits		4
Outdoor air flow		m3/h	2700
Outdoor sound pressure level		dB(A)	60.5
Outdoor sound power level		dB(A)	65
Throttle type			Capillary +EXV
Outdoor unit	Dimension(WxDxH)	mm	845x363x702
	Packing(WxDxH)	mm	965x395x755
	Net/Gross weight	kg	49/51.5
Refrigerant	Type		R410A
	GWP		2088
	Charged quantity	Kg	1.95
Design pressure		MPa	4.2/1.5
Refrigerant piping	Liquid side/ Gas side	mm(inch)	Φ9.52/Φ15.9(3/8"/5/8")
	Max. pipe length	m	50
	Max. difference in level	m	25
Ambient temperature	Cooling	℃	-15~50
	Heating	℃	-15~24