

Model			eiq-SSRFC24k
Average	Pdesignnc	kW	7.0
	SEER	W/W	6.1
	Energy Efficiency Class		A++
	Pdesignnh	kW	5.8
	SCOP	W/W	4.0
	Energy Efficiency Class		A+
	Tbiv	°C	-7
	Tol	°C	-15
Warmer	Pdesignnh	kW	5.6
	SCOP	W/W	5.1
	Energy Efficiency Class		A+++
	Tbiv	°C	2
Power supply (Indoor)		V,Hz,Ph	220~240,50,1
Power supply (Outdoor)		V,Hz,Ph	220~240,50,1
Cooling	Capacity	Btu/h	24000(4100-28000)
	Capacity	kW	7.03(1.20-8.21)
	Input	W	2170(400-3155)
	Current	A	9.9(1.8-14.4)
Heating	Capacity	Btu/h	24000(4100-29500)
	Capacity	kW	7.03(1.20-8.65)
	Input	W	1900(400-3090)
	Current	A	8.7(1.8-14.1)
Indoor fan motor	Model		ZKFP-124-8-2
	OldModel		WZDK124-38G
	Qty		1
	Input	w	141
	Capacitor	uF	---
	Speed(hi/mi/lo)	r/min	700/600/450
Indoor coil	a.Number of rows		2
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1.4
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ7,innergroove tube
	f.Coil length x height x width	mm	2010x210x26.74
	g.Number of circuits		10
Indoor air flow (Hi/Mi/Lo)		m3/h	1450/1250/1100
Indoor sound pressure level (Hi)		dB(A)	46/42/39
Indoor sound power level (Hi)		dB(A)	61
Indoor unit	Dimension (W x Dx H)(body)	mm	840x840x245
	Packing (W x Dx H)(body)	mm	900x900x257
	Dimension (W x Dx H)(panel)	mm	950x950x55
	Packing (W x Dx H)(panel)	mm	1035x1035x90
	Net/Gross weight(body)	kg	24/28
	Net/Gross weight	kg	5/8
Design pressure		MPa	4.2/1.5
Drainage water pipe dia.		mm	ODΦ32
Refrigerant piping	Liquid side/ Gas side	mm	Φ9.52/Φ15.9(3/8"/5/8")
Controller		Standard	Remote contorl
Operation temperature		°C	17~30
Room temperature	Cooling	°C	17~32
	Heating	°C	0~30