
N 50, Built-in oven, Stainless steel B6ACH7HH0B







Optional accessories

Z11AB15A0	Baking tray, non-stick ceramic coated	
Z11CB10E0	Baking tray, grey enamelled	
Z11CR10X0	Baking and roasting grid (standard)	
Z11GT10X3	Glass roasting dish, 5,4l	
Z11TF36X0	3 level telescopic rails, full ext	
Z11TI15X0	Cliprails	
Z1913X0	Baking Stone	
Z19DD10X0	Steam set for ovens	

- $\sqrt{\rm CircoTherm^{\odot}}$ our smart hot-air solution for simultaneous baking and roasting on up to three levels
- $\checkmark\,$ Dual cleaning options: Pyrolytic cleaning programmes just let the oven interior clean itself. EasyClean the quick and easy option for day to day maintenance.
- $\sqrt{\rm \ LCD-Display-simple,\ straightforward}$ with large characters for clear reading
- $\checkmark\,$ Home Connect rediscover your kitchen with our connected home appliances, from wherever you are.
- $\checkmark\,$ Clip-on Rail easily removed and installed telescopic rails for flexible use on all shelf levels

Features

Technical Data Color / Material Front : Stainless steel Construction type : Built-in Integrated Cleaning system : Hydrolytic, Pyrolytic Required niche size for installation (HxWxD) : $585-595 \times 560-568 \times$ 550 Dimensions of the product (mm) : $595 \times 594 \times 548$ Dimensions of the packed product (HxWxD) (mm) : 675 x 690 x 660 Control Panel Material : Glass Door Material : Glass Net weight (kg) : 41.197 Usable volume of cavity (I) : 71 Cooking method : Bottom heat, Bread Baking Setting, Conventional heat, Full width grill, Hot Air, Hot air grilling, Pizza setting First cavity material : Other Oven control : electronic Number of interior lights : 1 Approval certificates : CE, VDE Length of electrical supply cord (cm) : 120 EAN code : 4242004245834 Number of cavities (2010/30/EC) : 1 Energy efficiency class (2010/30/EC) : A Energy consumption per cycle conventional (2010/30/EC) : 1.04 Energy consumption per cycle forced air convection (2010/30/EC) : 0.81 Energy efficiency index (2010/30/EC) : 95.3 Connection rating (W) : 2990 Current (A) : 13 Voltage (V) : 220-240 Frequency (Hz) : 50; 60 Plug type : no plug



N 50, Built-in oven, Stainless steel В6АСН7ННОВ

Features

Design

- LCD-Display Control (white)
- Enamel grey
- Slide&Hide[®] with fixed handle

Features

- HomeConnect ready on WLAN
- Door lock during pyrolytic cleaning Control panel lock Automatic safety switch off Residual heat indicator Door contact switch
- Temperature proposal Actual temperature display Heating up indicator Sabbath setting Automatic start
- Interior halogen light

Cleaning

- Pyrolytic cleaning
- EasyClean

Programmes/functions


- Rapid heat
- Cooling fan
- 1 Clip rail, Stop function


Performance/technical information


- Energy efficiency rating (acc. EU Nr. 65/2014): A Energy consumption per cycle in conventional mode: 1.04 kWh Energy consumption per cycle in fan-forced convection mode: 0.81 kWh Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre
- Total connected load electric: 2.99 KW
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual

N 50, Built-in oven, Stainless steel В6АСН7ННОВ

Dimensioned drawings








measurements in mm

Installation with a hob.



measurements in mm

If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	37 mm	38 mm
Full surface Induction hob	47 mm	48 mm
Gas hob	30 mm	38 mm
Electric hob	27 mm	30 mm