N 50

















Included accessories

2 x combination grid, 1 x universal pan

Optional accessories

Z11TI15X0 Cliprails



- $\sqrt{\mbox{ CircoTherm}^{\mbox{\scriptsize @}}}$ the unique hot air-system for simultaneous baking and roasting on up to 3 levels
- $\sqrt{\mbox{ EasyClean}^{\mbox{\scriptsize @}}}$ this special cleaning aid provides uncomplicated, energy-saving cleaning of the oven interior.
- $\sqrt{}$ An environment-saving option for fast oven cleaning.
- $\sqrt{\text{Clip-on Rail easily removed}}$ and installed telescopic rails for flexible use on all shelf levels
- √ Hinged door

Features

Technical Data

Color / Material Front : Stainless steel Built-in / Free-standing : Built-in Integrated Cleaning system: Hydrolytic

Required niche size for installation (HxWxD) : $585-595 \times 560-568 \times 10^{-2}$

Dimensions of the product (mm) : $595 \times 594 \times 548$

Dimensions of the packed product (HxWxD) (mm) : $675 \times 690 \times 660$

Control Panel Material: Glass Door Material : Glass

Net weight (kg): 32.3 Usable volume (of cavity) - cavity 1 (I): 71

Cooking method: Conventional heat, Full width grill, Heißluft sanft,

Hot Air, Hot air grilling, Pizza setting First cavity material: Other

Temperature control : No control of the temperature

Number of interior lights: 1 Approval certificates : CE, VDE Length electrical supply cord (cm): 120 EAN code: 4242004225034 Number of cavities (2010/30/EC): 1

Energy efficiency class (2010/30/EC): A

Energy consumption per cycle conventional (2010/30/EC): 0.97 Energy consumption per cycle forced air convection (2010/30/EC):

Energy efficiency index (2010/30/EC): 95.3 Electrical connection rating (W): 2990

Current (A): 13 Voltage (V): 220-240 Frequency (Hz): 50; 60 Plug type: no plug



N 50 B1ACE4HN0B SINGLE OVEN

Features

Design

- LCD Display (White)
- Retractable controls dials, Bevelled oval controls
- Cavity inner surface: Enamel grey
- Drop down door
- Bar handle

Features

- Control panel lock
- Heating up indicator
- Interior halogen light
- Double glazed door

Cleaning

- EcoCleanDirect : back panel
- EasyClean
- Full glass inner door

Programmes/functions

- 6 heating methods: CircoTherm®, Top/bottom heat, Hot air grilling, Full surface grill, CircoTherm® intensive, CircoTherm® gentle
- Cooling fan

Accessories

- 1 Clip rail, Stop function
- 2 x combination grid, 1 x universal pan


Performance/technical information


Energy efficiency rating (acc. EU Nr. 65/2014): A
 Energy consumption per cycle in conventional mode: 0.97 kwh
 Energy consumption per cycle in fan-forced convection mode: 0.81 kwh

Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre


- Total connected load electric: 2.99 KW
- \bullet Temperature range 50 °C 275 °C
- Length of mains cable: 120 cm
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 594 mm x 548 mm
- Niche dimension (hxwxd): 585 mm - 595 mm x 560 mm - 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual

Dimensioned drawings





Installation with a hob.



measurements in mm