N 90, Built-in oven, 60 x 60 cm, Stainless steel B47CS34H0B



COOKING PASSION SINCE 1877













Ontional accessories

$$\label{eq:2.2} \begin{split} Z11AB15A0:, Z11CG10X0:, Z11CR10X0:, Z11GT10X3:, \\ Z11GU20X0:, Z11SZ00X0:, Z11SZ80X0: SeamlessCombination \\ 60+29cm, Z11SZ90X0: SeamlessCombination 60+45cm, \\ Z11TC10X0:, Z11TF36X0:, Z12CB10A0:, Z12CM10A0:, \\ Z12CP10A0:, Z12CQ10A0:, Z13CV05S0:, Z1913X0:, \\ Z19DD10X0: \end{split}$$

Built-in oven with Slide&Hide $^{\scriptsize @}$ - unrestricted access to the oven interior

- $\sqrt{\ }$ Slide&Hide® unrestricted access in the oven interior and easy handling due to rotating handle
- $\sqrt{\ }$ Eco Clean with Base Clean the duo that makes oven cleaning easier
- $\sqrt{\,}$ Shift Control fast navigation through menus and simple operation with the TFT display.
- $\sqrt{\ }$ Home Connect rediscover your kitchen with our connected home appliances, from wherever you are.
- $\sqrt{\ }$ Baking and Roasting Assistant your helper in the kitchen for ideal cooking times, temperatures, and modes for many dishes at your fingertips

Features

Technical Data

Color / Material Front : Stainless steel

Construction type: Built-in

Integrated Cleaning system : Catalytic all sides, Catalytic all sides Required niche size for installation (HxWxD) : $585-595 \times 560-568 \times 10^{-2}$

550

Dimensions : 595 x 596 x 548

Dimensions of the packed product (HxWxD) (mm) : $660 \times 690 \times 660$

Control Panel Material : Stainless steel

Door Material : Glass Net weight (kg) : 37.924 Usable volume of cavity (I) : 71

Cooking method: Bottom heat, Bread Baking Setting, Conventional heat, Defrost, Dough proving setting, Full width grill, Half width grill, Hot Air-Eco, Hot air grilling, low temperature cooking, Pizza setting

Temperature control : electronic Number of interior lights : 1 Approval certificates : CE, VDE

Length of electrical supply cord (cm) : 120

EAN code : 4242004236030 Number of cavities (2010/30/EC) : 1

Energy efficiency rating : A

Energy consumption per cycle conventional (2010/30/EC) : 0.90 Energy consumption per cycle forced air convection (2010/30/EC) :

0.7/

Energy efficiency index (2010/30/EC): 87.1

Connection rating (W): 3450

Current (A): 16 Voltage (V): 220-240 Frequency (Hz): 50; 60 Plug type: no plug





Features

Design

- 4.1" TFT colour and graphics display with ShiftControl
- Cavity inner surface: enamel anthracite
- Illuminated Shift Control
- Slide&Hide® with rotating handle
- We recommend you to choose complementary products within N90, in order to assure an optimal design combination of your Built-In appliances.

Features

- HomeConnect ready on WLAN
- Control panel lock
 Automatic safety switch off
 Residual heat indicator
 Start button
 Door contact switch
- Temperature proposal Actual temperature display Heating up indicator
- Baking and roasting assistant
- Interior halogen light, On/off button
- Electronic clock timer
- 4 shelf positions

Cleaning

- \bullet EcoClean Direct : ceiling, back panel, side liners
- EcoClean programme, Base Clean programme

Programmes/functions

- Oven with 13 main functions heating methods: CircoTherm[®], CircoTherm[®] Gentle, Top/bottom heat, Conventional heat Gentle, Circo-roasting, Full surface grill, Centre surface grill, CircoTherm[®] intensive, Bread baking, Bottom heat, Low temperature cooking, Defrost, Dough proving
- Rapid heat
- Cooling fan

Accessories

- 1-level flexible telescopic rail, full extension, Stop function
- 1 x combination grid, 1 x universal pan

Performance/technical information


Energy efficiency rating (acc. EU Nr. 65/2014): A
 Energy consumption per cycle in conventional mode: 0.9 kWh
 Energy consumption per cycle in fan-forced convection mode:
 0.74 kWh


Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre

- Total connected load electric: 3.45 KW
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 596 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm
- Please refer to the dimensions provided in the installation manual



Dimensioned drawings





If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

| Hob type | min. worktop thickness | |
|-------------------------------|------------------------|-------|
| | fitted | flush |
| Induction hob | 37 mm | 38 mm |
| Full surface Induction hob | 47 mm | 48 mm |
| Gas hob | 30 mm | 38 mm |
| Electric hob | 27 mm | 30 mm |