N 90, Built-in oven with steam function, 60 x 60 cm, Stainless steel B47FS34H0B













Z11AB15A0: Baking tray, non-stick ceramic coated, Z11CG10X0: Accessory, Z11GT10X3: Glass roasting dish, 5,4l, Z11GU20X0: Glasspan, Z11SZ00X0: SeamlessCombination mounting kit, Z11SZ80X0: SeamlessCombination 60 + 29cm, Z11SZ90X0: SeamlessCombination 60 + 45cm, Z12CB10A0: Baking tray, anthracite enamelled, Z12CM10A0: Moussaka pan, anthracite enamelled, Z12CP10A0: Pizza pan, anthracite enamelled, Z12CQ10A0: Grill tray, anthracite enamelled, Z13CR10X0: Baking and roasting grid (steam), Z13CV05S0: Cover Strip, Z13TC10X0: ComfortFlex Rail (1 level) f. steam

Built-in oven with FullSteam and SLIDE&HIDE® - combining all heating types and steam cooking in a single oven with unrestricted access

- $\sqrt{\mbox{Slide\&Hide}^{\mbox{\scriptsize @}}}$ unrestricted access in the oven interior and easy handling due to rotating handle
- $\sqrt{}$ Eco Clean with Base Clean the duo that makes oven cleaning
- $\sqrt{\ }$ Shift Control fast navigation through menus and simple operation with the TFT display.
- $\sqrt{}$ Home Connect rediscover your kitchen with our connected home appliances, from wherever you are.
- $\sqrt{\ }$ Baking and Roasting Assistant with Automatic Programmes the duo for optimal baking at your command

Technical Data

Color / Material Front : Stainless steel

Construction type: Built-in Door opening: Drop down

Required niche size for installation (HxWxD): 585-595 x 560-568 x

Dimensions of the packed product (HxWxD) (mm): 660 x 660 x 690

Control Panel Material: Stainless steel

Door Material: Glass Net weight (kg): 42.665 Approval certificates : CE, VDE

Length of electrical supply cord (cm): 120

EAN code: 4242004236047

Current (A): 16 Voltage (V): 220-240 Frequency (Hz): 50; 60 Plug type: no plug

Approval certificates : CE, VDE Number of cavities (2010/30/EC): 1

Usable volume (of cavity) - NEW (2010/30/EC): 71

Energy efficiency rating: A+

Energy consumption per cycle conventional (2010/30/EC): 0.87 Energy consumption per cycle forced air convection (2010/30/EC) :

Energy efficiency index (2010/30/EC): 81.2





N 90, Built-in oven with steam function, 60 x 60 cm, Stainless steel B47FS34H0B

COOKING PASSION SINCE 1877

Features

Design

- 4.1" TFT colour and graphics display with ShiftControl
- Cavity inner surface: enamel anthracite

Features

- HomeConnect ready on WLAN
- Control panel lock
 Automatic safety switch off
 Residual heat indicator
 Start button
 Door contact switch
- Temperature proposal Actual temperature display Heating up indicator automatic programmes:
- Baking and roasting assistant, Automatic programmes
- LED light, On/off button
- Water tank empty indicator
- Electronic clock timer

Cleaning

- EcoClean Direct : ceiling, back panel, side liners
- EcoClean programme, Base Clean programme

Programmes/functions

- Additional heating methods with steam: Steaming, Reheat with steam, Dough proving, Defrost
- Additional functions:
 De-scaling programme
 Drying function
- Automatic boiling point detection
- Number of automatic programmes: 30 PC
- Rapid heat
- Cooling fan

Accessories

- 1-level flexible telescopic rail, full extension, Stop function
- 1 x steam container, punched, size S, 1 x steam container, punched, size XL, 1 x steam container, unpunched, size S, 1 x grid, 1 x universal pan

Performance/technical information

Energy efficiency rating (acc. EU Nr. 65/2014): A+
 Energy consumption per cycle in conventional mode: 0.87 kWh
 Energy consumption per cycle in fan-forced convection mode: 0.69 kWh

Number of cavities: Main cavity Heat source: electrical Cavity volume: 71 litre


- 1 I Water tank capacity
- Location of water tank: Outside cavity
- Total connected load electric: 3.45 KW
- Temperature range 40 °C 250 °C
- 120 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 595 mm x 596 mm x 548 mm
- Niche dimension (hxwxd): 585 mm 595 mm x 560 mm 568 mm x 550 mm
- Please refer to the dimensions provided in the installation manual



N 90, Built-in oven with steam function, 60 x 60 cm, Stainless steel B47FS34H0B

COOKING PASSION SINCE 1877

Dimensioned drawings



If the appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

| Hob type | min. worktop thickness | |
|-------------------------------|------------------------|-------|
| | fitted | flush |
| Induction hob | 37 mm | 38 mm |
| Full surface Induction hob | 47 mm | 48 mm |
| Gas hob | 30 mm | 38 mm |
| Electric hob | 27 mm | 30 mm |

