


COOKING PASSION SINCE 1877





- $\sqrt{\,}$ CircoTherm® our smart hot-air solution for simultaneous baking and roasting on up to four levels
- $\sqrt{\,}$ Sous-vide prepare vacuum-sealed dishes with FullSteam for a new horizon of flavour.
- $\sqrt{\ }$ Eco Clean with Base Clean the duo that makes oven cleaning easier
- $\sqrt{}$ FullTouch Control simple, precise oven control by fingertip touch on the smooth surface of the high resolution TFT colour display.
- $\sqrt{}$ Home Connect rediscover your kitchen with our connected home appliances, from wherever you are.
- $\sqrt{\,}$ Baking and Roasting Assistant with Automatic Programmes the duo for optimal baking at your command
- $\sqrt{\,}$ Multipoint Meatprobe the thermometer helps the oven regulate the temperature and automatically adjust the cooking time
- $\sqrt{\,}$ LED lights Bright illumination exactly where you need it.





Features

Technical Data

Color / Material Front : Stainless steel

Construction type : Built-in Door opening : Drop down

Required niche size for installation (HxWxD) : 450-455 x 560-568 x

550

Dimensions of the product (mm) : $455 \times 596 \times 548$

Dimensions of the packed product (HxWxD) (mm) : $540 \times 660 \times 690$

Control Panel Material: Stainless steel

Door Material : Glass Net weight (kg) : 35.733 Approval certificates : CE, VDE

Length of electrical supply cord (cm): 150

EAN code: 4242004236412

Current (A): 16 Voltage (V): 220-240 Frequency (Hz): 50; 60 Plug type: no plug

Approval certificates : CE, VDE Number of cavities (2010/30/EC) : 1

Usable volume (of cavity) - NEW (2010/30/EC): 47

Energy efficiency class (2010/30/EC) : A+

Energy consumption per cycle conventional (2010/30/EC) : 0.73 Energy consumption per cycle forced air convection (2010/30/EC) :

0.61

Energy efficiency index (2010/30/EC): 81.3



Optional accessories

Z11AB15A0 : Baking tray, non-stick ceramic coated , Z11GT10X3 : Glass roasting dish, 5,4l , Z11GU20X0 : Glasspan , Z11SZ00X0 : SeamlessCombination mounting kit , Z11SZ60X0 : SeamlessCombination $45 + 14 \mathrm{cm}$, Z11SZ90X0 : SeamlessCombination $60 + 45 \mathrm{cm}$, Z12CB10A0 : Baking tray, anthracite enamelled , Z12CM10A0 : Moussaka pan, anthracite enamelled , Z12CP10A0 : Pizza pan, anthracite enamelled , Z12CQ10A0 : Grill tray, anthracite enamelled , Z13CR10X0 : Baking and roasting grid (steam) , Z13CV06S0 : Decor strip , Z13CX62X0 : Vacuum bags 180 x 280 mm, 100 pcs. , Z13CX64X0 : Vacuum bags 240 x 350 mm, 100 pcs. , Z13TC10X0 : ComfortFlex Rail (1 level) f. steam , Z13TC14X0 : ComfortFlex Rail (1)&racks,45cm f. steam

N 90, Built-in compact oven with steam function, Stainless steel C18FT56H0B

Feature:

Design

- 5.7" TFT colour and graphics display with FullTouch control
- Enamel anthracite
- Drop down door, SoftClose, soft opening
- Touch control
- We recommend you to choose complementary products within N90, in order to assure an optimal design combination of your Built-In appliances.

Features

- HomeConnect ready on WLAN
- Control panel lock Automatic safety switch off Residual heat indicator Start button Door contact switch
- Temperature proposal Actual temperature display Heating up indicator Sabbath setting automatic programmes:
- Baking and roasting assistant, Automatic programmes
- Water tank empty indicator
- MultiPoint MeatProbe
- LED light, On/off button
- Cooling fan
- Electronic clock timer
- 3 shelf positions

Cleaning

- EcoClean Direct : ceiling, back panel, side liners
- EcoClean programme, Base Clean programme
- Full glass inner door

Programmes/functions

- Compact steam oven with 13 main functions heating methods: CircoTherm®, CircoTherm® Gentle, Top/bottom heat,
 Conventional heat Gentle, Circo-roasting, Full surface grill, Centre surface grill, CircoTherm® intensive, Bread baking, Bottom heat,
 Low temperature cooking, Plate warming, Keep warm
- Additional heating methods with steam: Steaming, Reheat, Dough proving, Defrost
- Additional functions: De-scaling programme Drying function Automatic boiling point detection
- Number of automatic programmes: 30 PC
- Rapid heat

Accessories

• 1 x steam container, punched, size S, 1 x steam container, punched, size XL, 1 x steam container, unpunched, size S, 1 x grid, 1 x universal pan

Performance/technical information


 Energy efficiency rating (acc. EU Nr. 65/2014): A+ Energy consumption per cycle in conventional mode: 0.73 kWh Energy consumption per cycle in fan-forced convection mode: 0.61 kWh Number of cavities: Main cavity Heat source: electrical Cavity volume: 47 litre


- Temperature range 40 °C 250 °C
- 1 | Water tank capacity
- Location of water tank: Outside cavity
- Power cord length 150 cm Cable length
- Nominal voltage: 220 240 V
- Appliance dimension (hxwxd): 455 mm x 596 mm x 548 mm
- Please refer to the dimensions provided in the installation manual

N 90, Built-in compact oven with steam function, Stainless steel C18FT56H0B

Dimensioned drawings

Installation with a hob.





measurements in mm

If the compact appliance will be installed underneath a hob, the following worktop thicknesses (including substructure if necessary) must be taken into account.

Hob type	min. worktop thickness	
	fitted	flush
Induction hob	42 mm	43 mm
Full surface Induction hob	52 mm	53 mm
Gas hob	32 mm	43 mm
Electric hob	32 mm	35 mm

