

Product Highlights

- **HD resolution**
High-resolution images ensure that you capture the details that you need
- **Reliable 24-Hour Surveillance**
Infrared LED illuminators provide a clear picture at night for dependable 24-hour surveillance
- **Outdoor Installation**
The IP66 certified enclosure can be mounted outdoors and operated at temperatures from -20 to 50 °C



DCS-7110

HD Outdoor Day & Night IP Camera

Key Features

- 1/4" megapixel progressive CMOS sensor
- HD resolution: 1280 x 800 (megapixel) at 30 fps
- IP-66 certified weatherproof housing
- PoE powered – no need for a separate power supply
- Built-in IR LEDs for Day & Night operation (15 m. illumination distance)
- Built-in IR-Cut Removable (ICR) filter, for enhanced colour rendering in the day and good results in low light conditions
- Simultaneous streaming in H.264, MJPEG and MPEG-4 compression
- Hardware-based motion detection
- Tamper detection
- IPv6 support
- Privacy mask function
- 3GPP support – watch live video from a compatible smartphone
- Digital I/O support for sensors and alarms
- Open Network Video Interface Forum (ONVIF) compliant
- D-ViewCam™ (DCS-100) monitoring software included (support for up to 32 cameras)

The D-Link DCS-7110 is a high-definition outdoor IP Camera, equipped with a 1/4" megapixel CMOS sensor and 4 mm F1.5 fixed-focus lens. The DCS-7110 is capable of capturing videos in both dark and light environments with its built-in IR LEDs and removable IR-cut (ICR) filter, which provides high quality videos day or night. The ICR filter can be manually applied via the web or set to automatically adjust based on lightning conditions. Capture crisp color images during the daytime and detailed greyscale images at night or in or low-light conditions.

Multiple Video Streams

The DCS-7110 supports simultaneous streaming of H.264, MPEG-4, and MJPEG video to provide both high-quality and bandwidth-efficient compression formats. MJPEG delivers excellent file integrity, ideal for situations which require extensive image detail. H.264 produces a small file size, making it more useful for extended recording or for use in low-bandwidth networks. Additionally, the DCS-7110 supports multicast H.264 streaming, allowing users to view the camera images by subscribing to a multicast group on the network.

Flexible Connectivity

The DCS-7110 includes input and output ports for connectivity to external devices such as IR sensors, switches, and alarm relays. It also comes with an RS-485 interface, providing connectivity to an optional pan/tilt enclosure. The DCS-7110 also incorporates Power over Ethernet (PoE), allowing it to be easily installed in a variety of locations without the need for supplemental power cabling.

Tamper Detection

Designed to be mounted outdoors, the DCS-7110 includes an IP66 certified enclosure which protects against the environmental elements. This makes it suitable for tamper-prone locations such as transportation hubs, schools, or correctional facilities. The tamper detection feature can sense whenever the camera has been redirected, de-focused, blocked or spray-painted and respond promptly with a visible or audible alarm.

Removable IR-Cut Filter

The DCS-7110 comes with a ICR Filter which can be manually applied via a web interface or can be set to automatically adjust based on lighting conditions. This feature allows the camera to capture crisp colour images during the daytime and greyscale images at night.

Open Network Video Interface Forum (ONVIF) compliant

The Open Network Video Interface Forum (ONVIF) is standards relating to open IP video networking. The DCS-7110 is ONVIF compliant and therefore interoperable with other manufacturer's products on the same network such as cameras, storage systems, video analytics products and Video Management Systems.

Centralised management with D-ViewCam™

The included D-Link D-ViewCam™ IP camera surveillance software is a comprehensive surveillance system designed to centrally manage multiple IP cameras. Supporting up to 32 IP cameras, D-ViewCam™ is compatible with all current D-Link IP cameras, Video Servers and offers digital monitoring and recording capabilities of video, audio, and events for various security applications. This software provides users with a wide array of features for added convenience, including video recording, playback, video live view, offering users powerful surveillance software that's easy to use.



If the worst should happen to your network you need the very best support and fast. Downtime costs your business money. D-Link Assist maximises your uptime by solving technical problems quickly and effectively. Our highly trained technicians are on standby around the clock, ensuring that award-winning support is only a phone call away.

With a choice of three affordable service offerings covering all D-Link business products, you can select the package that suits you best:

D-Link Assist Gold - for comprehensive 24-hour support

D-Link Assist Gold is perfect for mission-critical environments where maximum uptime is a high priority. It guarantees four hour around-the-clock response. Cover applies 24/7 for every day of the year including holidays.

D-Link Assist Silver - for prompt same-day assistance

D-Link Assist Silver is designed for 'high availability' businesses that require rapid response within regular working hours. It provides a four hour response service Monday to Friday from 8am to 5pm, excluding holidays.

D-Link Assist Bronze - for guaranteed response on the next business day

D-Link Assist Bronze is a highly cost-effective support solution for less critical environments. Response is guaranteed within eight business hours Monday to Friday from 8am to 5pm, excluding holidays.

D-Link Assist can be purchased together with any D-Link business product. So whether you're buying switching, wireless, storage, security or IP Surveillance equipment from D-Link, your peace of mind is guaranteed. D-Link Assist also offers installation and configuration services to get your new hardware working quickly and correctly.

Technical Specifications

Video Algorithms Supported	<ul style="list-style-type: none"> • H.264/MPEG4/MJPEG format compression simultaneously • JPEG for still image • H.264/MPEG-4 multicast streaming 	
Hardware Profile	<ul style="list-style-type: none"> • Sensor: 1/4" megapixel progressive CMOS sensor • SDRAM: 256 Mbytes • Flash Memory: 128 Mbytes • ICR: Built-in Infrared-Cut filter Removable module 	<ul style="list-style-type: none"> • Lens: 4 mm fixed lens , F1.5 • View Angle: Horizontal 65.4 degrees • IR LED: 15 meter illumination distance and light sensor
Image Features	<ul style="list-style-type: none"> • Adjustable image size, quality, and bit rate • Time stamp and text overlays • 3 configurable motion detection windows 	<ul style="list-style-type: none"> • 5 configurable privacy masks • Flip & mirror • Configurable brightness, saturation, contrast, sharpness
Number of Ports	<ul style="list-style-type: none"> • 176x144 @ 30 fps • 320x240 @ 30 fps • 640x480 @ 30 fps 	<ul style="list-style-type: none"> • 1280x720 @ 30 fps • 1280x800 @ 30 fps
Network Protocols	<ul style="list-style-type: none"> • IPv4, IPv6 • TCP/IP, UDP, ICMP • DHCP Client • NTP Client (D-Link) • DNS Client, DDNS Client (D-Link) • SMTP Client • FTP Client • HTTP / HTTPS • Samba Client • PPPoE • UPnP Port Forwarding 	<ul style="list-style-type: none"> • RTP / RTSP / RTCP • IP filtering • 3GPP • LLTD • CoS/QoS • SNMP/IGMP • SNMP • IGMP • 802.1x • ONVIF Compliant
3GPP Mobile Surveillance	<ul style="list-style-type: none"> • Packet Video Player 3.0 • QuickTime 6.5 • Real Player 10.5 	
System Requirements for Viewing	<ul style="list-style-type: none"> • Internet Explorer 6 or later 	
D-ViewCam™ System Requirements	<ul style="list-style-type: none"> • Operating System: Microsoft Windows® 7 / Vista / XP 	<ul style="list-style-type: none"> • Web Browser: Internet Explorer 6 or higher • Protocol: Standard TCP/IP
Power Input	<ul style="list-style-type: none"> • 12 VDC 1.25 A, 240 VAC 50/60 Hz 	<ul style="list-style-type: none"> • PoE: IEEE 802.3af
Maximum Power Consumption	<ul style="list-style-type: none"> • 6 W 	
Operating Temperature	<ul style="list-style-type: none"> • -20 to 50 °C (-4 to 122 °F) 	
Storage Temperature	<ul style="list-style-type: none"> • -20 to 70 °C (-4 to 158 °F) 	
Humidity	<ul style="list-style-type: none"> • 783 g 	
Certifications	<ul style="list-style-type: none"> • CE (Class A) • CE LVD (EN60965-1) • FCC (Class A) • ICES-003, ICES-006 • C-Tick 	
Camera Dimensions		



For more information: www.dlink.com

D-Link European Headquarters. D-Link (Europe) Ltd., D-Link House, Abbey Road, Park Royal, London, NW10 7BX. Specifications are subject to change without notice. D-Link is a registered trademark of D-Link Corporation and its overseas subsidiaries. All other trademarks belong to their respective owners. ©2012 D-Link Corporation. All rights reserved. E&OE.

Updated 28/01/2013