



DIH 82G1A B**12NC/Fx: F171264****GTIN (EAN) code:
5054645712649**

DIMENSION	MEASURE	DIMENSION	MEASURE
OVERALL CABINET		APPLIANCE	
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0 mm	Height of the front	0 mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	0 mm	Width of the front	0 mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	0 mm	Depth of the front	0 mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0 mm	Maximum depth all protruding elements, e.g. handles, controls	0 mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	0 mm	Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	0 mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	0 mm	Projection of front in relation to housing of appliance	0 mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0 mm	Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	0 mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	0 mm	When product panel is missing, set to 0	0 mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	0 mm	Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	0 mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0 mm	Height from bearing area of appliances and lower handle	0 mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	0 mm	Frontal handle thickness	0 mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	0 mm	Frontal handle width	0 mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0 mm	MIN Height of the product body	0 mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	0 mm	MAX Height of the product body	0 mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	0 mm	Width of the product body	0 mm
Space in front, which is required to install bottom trim	0 mm	Depth of the product body	0 mm
Indicates whether a ventilation opening is needed or not. Default is "N"	-	Full depth of product excluding protruding interface elements	0 mm
WALL CABINET (vent-shaft incoming)		MIN depth between plinth return and front	0 mm
Indicates the position of the freespace for the inbound airflow (wall cabinet)	-	MAX depth between plinth return and front	0 mm
Minimum space or inbound ventilation (wall cabinet)	0 mm	Height MIN Plinth return. This dimension is taken by minimum appliance height	0 mm
Minimum area for inbound ventilation cavity (wall cabinet)	0 cm ²	Height MAX Plinth return. This dimension is taken at maximum appliance height	0 mm
WALL CABINET (vent-shaft outgoing)		Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	-
Indicates the position of the freespace for the outbound airflow (wall cabinet)	-	Appliance Flap door	
Minimum space or outbound ventilation (wall cabinet)	0 mm	Projection of the opened flap in relation to bearing area	0 mm
Minimum area for outbound ventilation cavity (wall cabinet)	0 cm ²	Maximum angle when flap door is opened totally	0 mm
TALL CABINET (vent-shaft incoming)		Appliance Side swing door	
Indicates the position of the freespace for the inbound airflow (tall cabinet)	-	Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted	0 mm
Minimum space for inbound ventilation (tall cabinet)	0 mm	Lateral projection of opened front at the side where the hinge is fixed	0 mm
Minimum area for inbound ventilation cavity (tall cabinet)	0 cm ²	Maximum angle when door is opened totally	0 mm
TALL CABINET (vent-shaft outgoing)		Appliance other	
Indicates the position of the freespace for the outbound airflow (tall cabinet)	-	Depth from front end of the niche to the front end of the freespace of the retrace	0 mm
Minimum space for outbound ventilation (tall cabinet)	0 mm	Height from niche to bottom end of freespace for the retrace	0 mm
Minimum area for outbound ventilation cavity (tall cabinet)	0 cm ²		
BASE CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (base cabinet)	-		
Minimum space for inbound ventilation (base cabinet)	0 mm		
Minimum area for inbound ventilation cavity (base cabinet)	0 cm ²		
BASE CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (base cabinet)	-		
Minimum space for outbound ventilation (base cabinet)	0 mm		
Minimum area for outbound ventilation cavity (base cabinet)	0 cm ²		