



HO 255H X UK**12NC/Fx: F170770****GTIN (EAN) code:
5054645707706**

| DIMENSION | MEASURE | DIMENSION | MEASURE |
|--|---------------------|---|---------|
| OVERALL CABINET | | APPLIANCE | |
| MIN Height of the wall cabinet niche, including all required space for installation or ventilation | 0 mm | Height of the front | 595 mm |
| MIN Height of the tall cabinet niche, including all required space for installation or ventilation | 583 mm | Width of the front | 595 mm |
| MIN Height of the base cabinet niche, including all required space for installation or ventilation | 600 mm | Depth of the front | 20 mm |
| MAX Height of the wall cabinet niche, including all required space for installation or ventilation | 0 mm | Maximum depth all protruding elements, e.g. handles, controls | 53 mm |
| MAX Height of the tall cabinet niche, including all required space for installation or ventilation | 585 mm | Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees | 55 mm |
| MAX Height of the base cabinet niche, including all required space for installation or ventilation | 601 mm | Projection of front in relation to housing of appliance | 20 mm |
| MIN Width of the wall cabinet niche, including all required space for installation or ventilation | 0 mm | Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable | 5 mm |
| MIN Width of the tall cabinet niche, including all required space for installation or ventilation | 560 mm | When product panel is missing, set to 0 | 97 mm |
| MIN Width of the base cabinet niche, including all required space for installation or ventilation | 560 mm | Space in front, which is required to guarantee full operability. The most protruding part gives this dimension | 460 mm |
| MAX Width of the wall cabinet niche, including all required space for installation or ventilation | 0 mm | Height from bearing area of appliances and lower handle | 443 mm |
| MAX Width of the tall cabinet niche, including all required space for installation or ventilation | 568 mm | Frontal handle thickness | 25 mm |
| MAX Width of the base cabinet niche, including all required space for installation or ventilation | 568 mm | Frontal handle width | 486 mm |
| MIN Depth of the wall cabinet niche, including all required space for installation or ventilation | 0 mm | MIN Height of the product body | 570 mm |
| MIN Depth of the tall cabinet niche, including all required space for installation or ventilation | 560 mm | MAX Height of the product body | 570 mm |
| MIN Depth of the base cabinet niche, including all required space for installation or ventilation | 560 mm | Width of the product body | 558 mm |
| Space in front, which is required to install bottom trim | 9 mm | Depth of the product body | 548 mm |
| Indicates whether a ventilation opening is needed or not. Default is "N" | Yes | Full depth of product excluding protruding interface elements | 570 mm |
| WALL CABINET (vent-shaft incoming) | | Appliance can be used as base for other appliances from the same manufacturer. Default is "No" | No |
| Indicates the position of the freespace for the inbound airflow (wall cabinet) | Rear | Appliance Flap door | |
| Minimum space or inbound ventilation (wall cabinet) | 0 mm | Projection of the opened flap in relation to bearing area | 0 mm |
| Minimum area for inbound ventilation cavity (wall cabinet) | 0 cm ² | Maximum angle when flap door is opened totally | 89 mm |
| WALL CABINET (vent-shaft outgoing) | | Appliance Side swing door | |
| Indicates the position of the freespace for the outbound airflow (wall cabinet) | Rear | Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted | 0 mm |
| Minimum space or outbound ventilation (wall cabinet) | 0 mm | Lateral projection of opened front at the side where the hinge is fixed | 0 mm |
| Minimum area for outbound ventilation cavity (wall cabinet) | 0 cm ² | Maximum angle when door is opened totally | 0 mm |
| TALL CABINET (vent-shaft incoming) | | Appliance other | |
| Indicates the position of the freespace for the inbound airflow (tall cabinet) | Rear | Depth from front end of the niche to the front end of the freespace of the retrace | 428 mm |
| Minimum space for inbound ventilation (tall cabinet) | 40 mm | Height from niche to bottom end of freespace for the retrace | 525 mm |
| Minimum area for inbound ventilation cavity (tall cabinet) | 150 cm ² | | |
| TALL CABINET (vent-shaft outgoing) | | | |
| Indicates the position of the freespace for the outbound airflow (tall cabinet) | Rear | | |
| Minimum space for outbound ventilation (tall cabinet) | 0 mm | | |
| Minimum area for outbound ventilation cavity (tall cabinet) | 150 cm ² | | |
| BASE CABINET (vent-shaft incoming) | | | |
| Indicates the position of the freespace for the inbound airflow (base cabinet) | Rear | | |
| Minimum space for inbound ventilation (base cabinet) | 40 mm | | |
| Minimum area for inbound ventilation cavity (base cabinet) | 150 cm ² | | |
| BASE CABINET (vent-shaft outgoing) | | | |
| Indicates the position of the freespace for the outbound airflow (base cabinet) | Rear | | |
| Minimum space for outbound ventilation (base cabinet) | 0 mm | | |
| Minimum area for outbound ventilation cavity (base cabinet) | 150 cm ² | | |