



HOI68PT1SXUK**12NC/Fx: F168631****GTIN (EAN) code:
5054645686315**

DIMENSION	MEASURE	DIMENSION	MEASURE
OVERALL CABINET		APPLIANCE	
MIN Height of the wall cabinet niche, including all required space for installation or ventilation	0 mm	Height of the front	597 mm
MIN Height of the tall cabinet niche, including all required space for installation or ventilation	583 mm	Width of the front	595 mm
MIN Height of the base cabinet niche, including all required space for installation or ventilation	595 mm	Depth of the front	20 mm
MAX Height of the wall cabinet niche, including all required space for installation or ventilation	0 mm	Maximum depth all protruding elements, e.g. handles, controls	47 mm
MAX Height of the tall cabinet niche, including all required space for installation or ventilation	585 mm	Lateral clearance between front edge and most protruding elements which avoid to open a neighbour front more than 90 degrees	47 mm
MAX Height of the base cabinet niche, including all required space for installation or ventilation	596 mm	Projection of front in relation to housing of appliance	18 mm
MIN Width of the wall cabinet niche, including all required space for installation or ventilation	0 mm	Projection of front in relation to bearing area of the appliance. Taken at minimum height of appliance, if height is adjustable	7 mm
MIN Width of the tall cabinet niche, including all required space for installation or ventilation	560 mm	When product panel is missing, set to 0	97 mm
MIN Width of the base cabinet niche, including all required space for installation or ventilation	560 mm	Space in front, which is required to guarantee full operability. The most protruding part gives this dimension	462 mm
MAX Width of the wall cabinet niche, including all required space for installation or ventilation	0 mm	Height from bearing area of appliances and lower handle	461 mm
MAX Width of the tall cabinet niche, including all required space for installation or ventilation	568 mm	Frontal handle thickness	47 mm
MAX Width of the base cabinet niche, including all required space for installation or ventilation	568 mm	Frontal handle width	488 mm
MIN Depth of the wall cabinet niche, including all required space for installation or ventilation	0 mm	MIN Height of the product body	572 mm
MIN Depth of the tall cabinet niche, including all required space for installation or ventilation	550 mm	MAX Height of the product body	572 mm
MIN Depth of the base cabinet niche, including all required space for installation or ventilation	550 mm	Width of the product body	546 mm
Space in front, which is required to install bottom trim	10 mm	Depth of the product body	543 mm
Indicates whether a ventilation opening is needed or not. Default is "N"	Yes	Full depth of product excluding protruding interface elements	564 mm
WALL CABINET (vent-shaft incoming)		Appliance can be used as base for other appliances from the same manufacturer. Default is "No"	No
Indicates the position of the freespace for the inbound airflow (wall cabinet)	Rear	Appliance Flap door	
Minimum space or inbound ventilation (wall cabinet)	0 mm	Projection of the opened flap in relation to bearing area	0 mm
Minimum area for inbound ventilation cavity (wall cabinet)	0 cm ²	Maximum angle when flap door is opened totally	89 mm
WALL CABINET (vent-shaft outgoing)		Appliance Side swing door	
Indicates the position of the freespace for the outbound airflow (wall cabinet)	Rear	Lateral projection of front incl. controls when door is opened totally. At the side where the hinge is mounted	0 mm
Minimum space or outbound ventilation (wall cabinet)	0 mm	Lateral projection of opened front at the side where the hinge is fixed	0 mm
Minimum area for outbound ventilation cavity (wall cabinet)	0 cm ²	Maximum angle when door is opened totally	0 mm
TALL CABINET (vent-shaft incoming)		Appliance other	
Indicates the position of the freespace for the inbound airflow (tall cabinet)	Rear	Depth from front end of the niche to the front end of the freespace of the retrace	345 mm
Minimum space for inbound ventilation (tall cabinet)	30 mm	Height from niche to bottom end of freespace for the retrace	537 mm
Minimum area for inbound ventilation cavity (tall cabinet)	150 cm ²		
TALL CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (tall cabinet)	Rear		
Minimum space for outbound ventilation (tall cabinet)	0 mm		
Minimum area for outbound ventilation cavity (tall cabinet)	150 cm ²		
BASE CABINET (vent-shaft incoming)			
Indicates the position of the freespace for the inbound airflow (base cabinet)	Rear		
Minimum space for inbound ventilation (base cabinet)	30 mm		
Minimum area for inbound ventilation cavity (base cabinet)	150 cm ²		
BASE CABINET (vent-shaft outgoing)			
Indicates the position of the freespace for the outbound airflow (base cabinet)	Rear		
Minimum space for outbound ventilation (base cabinet)	0 mm		
Minimum area for outbound ventilation cavity (base cabinet)	150 cm ²		