VR SHXMTFF C

VERTICO Shower Range Vertico Thermostatic Exposed Bar Valve with Ad-

justable Riser and Multi Function Handset Chrome

acificati



Features:


- 15mm inlet connections
- Thermostatic cartridge with preset temperature stop at 38°C, can be over-ridden to a maximum of 46°C
- Dual control flow and temperature are controlled separately
- Automatic shut-off in the event of hot or cold water supply failure
- Supplied with a wall mount 12 fixing kit for easier first fit


Product Certifications:

9.5 L/Min

Specification				
Style:	Contemporary			
Finish/Colour:	Chrome			
Main Construction Material:	Brass			
No of Controls:	2			
Shower Type:	Bar Shower			
Shower Head Type:	Handset			
Valve/Cartridge Type:	Thermostatic			
Maximum Hot Water Supply Temperature ^o C:	80			
Maximum Static Pressure: (bar)	10			
Plumbing System Suitability:	All - Ideally Balanced			
Working Pressure Range:	Min. 0.5 Bar - Max. 5.0 bar			
Connection Inlet:	15mm Compression			
Connection Outlet:	N/A			
Isolation Valve Included:	No			
Check Valve Included:	Yes			

Dimensions (measurements in mm)





D4

For more products, visit our website: <u>http://www.bristan.com</u>

SF

	Flow Rates (l/min)							
	System Pressure (bar)	0.2	0.5	1	2	3	5	
ECCA B. AND	Through Handset (mixed)	1.8	3.4	5.3	7.5	9.5	12.1	
TECHNICAL DATA	AST DUAL PA		3 R		574			

Bristan, Birch Coppice Business Park, Dordon, Tamworth, B78 ISG. Telephone: 0844 701 6274. Facsimile: 0844 701 6275. Web Site: www.bristan.com Email: enquire@bristan.com. The information contained on this page was correct at date of issue. Fitting Dimensions are provided as a guide only. Some variation may occur due to manufacturing tolerances. Bristan pursues a policy of continuing improvement in design and performance of its products and so reserves the right to change specifications without prior notice.

RAN