electric

WIFI Smart AC Adaptor Model: IQ-ACWIFISMART



Thank you for choosing ElectrIQ

Please read this user manual before using this WIFI Smart AC Adaptor and keep it safe for future reference.

Visit our page www.electrlQ.co.uk for our entire range of Intelligent Electricals

APP Download

You can download the APP for this device from either the Apple APP Store or Google Play Store. The APP can be found by searching for "WIFI AC" in the Apple App store for "ACC WiFi control" in the Google Play store or by scanning the below QR Code:





Installing the Smart Kit

1. Open the panel of the indoor unit to find the installation port on the right hand side.



2. Loosen the screw and remove the blanking cap. This cap and screw are no longer required but can be retained should you ever want to remove the Smart WIFI adaptor.



3. Insert the Smart WIFI adaptor into the slot, making sure the side with "Smart Kit" printed on is facing outwards.



4. Open the App on your mobile device and follow the prompts to register and log in.

WÎFI AC	WÎFI AC	WÎFI AC
E-mail address	E-mail address	₩ ••••••@ .com
Password	Password	∞,
Login	Confirm Password	Login
Register for WIFI AC Help Center	Already have an account here?	Register for WIFI AC Help Center

5. Once you have logged in you can add your device. Click on the "AC Management" button:



6. Click the "+ ADD AC" button:



7. Name your AC and then click the "Scan Quick Response Code". This will then allow you to scan the QR code on the bottom left of the AC unit:

AC MANAGEMENT	
ACINFORMATION	
● ADD AC	
ASSIGN USER	
⊕ ADD USER	
Bedrooml	
130930010037 039837	
Scan Quick Response Code	
ок	
cancel	

 Multiple users can be set up to be able to control the device by using the "+ ADD USER" button and adding their details into the fields as prompted. NOTE: New users must have an already registered account. Only the primary user can add users.



AC MANAGEMENT	
AC INFORMATION	
Bedroom1 130930010037 • ADD AC	正常 jimyung@163.com
ASSIGN USER	
ADD USER	
@com	
Bedroot	mi √
OK OK	~
cane	el

Connecting AC to Network

Before you can control your device, it must be connected to your WIFI network. The process for connecting it using an Android or iOS device is slightly different so please follow the relevant instructions for your mobile device operating system.

Android Devices

1. Open the WIFI AC App on your device and click on the "Help Centre" button:



2. Select the AC Connect network button:

WIFI AC
₩ *** [*] **@ .com
∽,
Login
AC Connect network
Forgot for password
cancel

3. Select your AC unit in the top box then the desired WIFI network from the list of available options, enter the password, then click Next Step:

AC Connect netwo	ork 🕽	
SELECT AC		
icongo_ *	-	
Select Network		
iNetword	-	
	a	
CMCC-AUTO	R	
cloudcenter	A	
CMCC-AUTO	a	
leader		
Enter the password		
Please enter the correct password		
Next Step		

4. Your AC unit will now be connected to your device and ready to control using the WIFI AC App.

iOS Devices

1. Open the WIFI AC App on your device and click on the "Help Centre" button:



2. Select the AC Connect network button:

WÎFI AC
******@ .com
∽~
Login
AC Connect network
Forgot for password
cancel

3. You will now be prompted to connect to the AC unit using the WIFI settings in your device:

<	CONNECT AC	
	Choose wifi ssid	
	Set WiFi to link with "icongo-*"	
1.		
Ι.		
	1.In System WIFI Setting,chose	
	2.Reenter while your device	
	connected to icongo-*	
1		

4. Close the WIFI AC App and open the settings menu on your mobile device:



5. Select your AC unit from the list of devices:

<pre>Settings WIFI</pre>	
WIFI	
✓ icongo_*	∻ (i)
Choose WIFI	
and-Business	∻ (i)
chigowifi319	? (i)
chigowifi321	? (i)
iNetword	₽ 🗢 (j)
CMCC	∻ (i)
CMCC-AUTO	₽ ≈ (i)
CMCC-WIFI	₽ 🗢 (j)
icongo_center	₽ ╤ (j
leader	₽ ╤ (j)
TP-LINK_4G_982D8C	₽ ≈ (j)

6. Re-open the WIFI AC app and select your desired WIFI Network:

?
?
@

7. Enter the password and click connect. Your device will now be connected to the network:



Controlling Your AC

1. Turn on the APP on your mobile device and log into your account:



2. Click on the 🔯 icon to select your AC unit in the device list:



3. You can now alter all the desired parameters of the device using the APP:

ROOM TEMP : 10:0	<u>. </u>	•
(+)		° 🖂
FAN SPEED		
AUTO	COOL	HEAT
FAN	D	RY
TURBO		SLEEP
AC CONTROL A	C MANAGEMENT	MY ACCOUNT

Settings



NOTE: Settings may vary from unit to unit. Please consult the user manual for your AC unit for the full details of the corresponding modes and functions.

Troubleshooting

- AC won't connect to network / App The AC has lost connection to the network. Reset the AC unit and reconnect using the above process from the beginning.
- How to reset AC Unit Set temperature on remote to 25 then press FAN SPEED SWING – AIR FLOW – then set temperature to 27 and press FAN SPEED – SWING – AIR FLOW. If this sequence is done within 10 seconds the unit will reset.

Specifications

Standard: IEEE 802.11 b/g/n Antenna type: Internal PCB Antenna WiFi Frequency: 2.4G Max Transmitted Power: 16dBm Max Operating Temp.: -5°C – 45°C Operating Humidity: 10% - 85% Power Input: DC 5V/200mA



PRODUCT DISPOSAL

Do not dispose this product as unsorted municipal waste. Collection of such waste must be handled separately as special treatment is necessary.

Recycling facilities are now available for all customers at which you can deposit your old electrical products. Customers will be able to take any old electrical equipment to participating civic amenity sites run by their local councils. Please remember that this equipment will be further handled during the recycling process, so please be considerate when depositing your equipment. Please contact the local council for details of your local household waste recycling centres.

electriQ UK SUPPORT

www.electriQ.co.uk/support

Complete online support form on: www.electriQ.co.uk/support

Customer Service Line: 0871 620 1057 Office hours: 9AM – 5PM Monday to Friday

> www.electriQ.co.uk Unit 2, The Nursery Berristow Lane South Normanton Derbyshire DE55 2FX