electric

USER MANUAL



electriQ WALL MOUNTED AIR CONDITIONER WITH HEAT PUMP, PTC HEATER AND WIFI SMART APP IQOOL-SMART12HP IQOOL-SMART15HP

Thank you for choosing electriQ

Please read this user manual before using this innovative Air Conditioner and keep it safe for future reference.

Visit our page www.electriQ.co.uk for our entire range of Intelligent Electricals

SETTLING IN OK?

We hope this has been helpful to you.

We would love to see how you're getting on with your new purchase, so please share any snaps you have on the platform of your choice below.

Our community awaits your uploads - Snap, tag and hashtag away!



@electriQUK #electriQUK

WE'RE HERE TO HELP

Should you have any problems or questions with your purchase, please contact a member of our customer service team.

© 0330 390 3061

support@electriQ.co.uk

Mon-Fri | 9am to 5pm

Unit J6, Lowfields Business Park, Lowfields Way, Elland West Yorkshire, HX5 9DA

CONTENTS

SAFETY INSTRUCTIONS	3
PRODUCT OVERVIEW	5
PRODUCT DIAGRAM	5
FEATURES	6
WHATS INCLUDED	6
INSTALLATION	7
TOOLS REQUIRED	7
INSTALLATION	8
ATTACHING THE BOTTOM COVER	11
OPERATION	12
CONTROL PANEL	12
REMOTE CONTROL	12
FUNCTIONS	12
WIFI SETUP AND SMART FEATURES	15
SETUP	15
CONTROLLING YOUR DEVICE THROUGH THE APP	20
SMART SCENES / AUTOMATION	22
TROUBLESHOOTING	25
TROUBLESHOOTING	25
ERROR CODES	26
TECHNICAL DATA	27
UK SUPPORT	28

SAFETY WARNING IMPORTANT!

AIR CONDITIONERS MUST ALWAYS BE STORED AND TRANSPORTED UPRIGHT, OTHERWISE IRREPARABLE DAMAGE MAY BE CAUSED TO THE COMPRESSOR; IF IN DOUBT WE SUGGEST WAITING AT LEAST 24 HOURS FOLLOWING INSTALLTION BEFORE STARTING THE UNIT.



- Carefully read the instructions before installing and/or operating the unit
- This appliance is for indoor use only.
- This unit must be only connected to a 220-240 V / 50 Hz earthed outlet.
- Installation must be in accordance with regulations of the country where the unit is used.
- If you are in any doubt about the suitability of your electrical supply have it checked and, if necessary, modified by a qualified electrician.
- This air conditioner has been tested and is safe to use. However, as with any electrical appliance use it with care.
- Disconnect the power from the appliance before dismantling, assembling or cleaning.
- Avoid touching any moving parts of the appliance.
- Never insert fingers, pencils or any other objects though the guard.
- This appliance is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities. It is also not intended for use by those with a lack of experience and knowledge, unless they have been given supervision or instruction concerning the use of the appliance by a person responsible for their safety.
- Do not leave children unsupervised with this appliance.
- Do not clean the unit by spraying it or immersing it in water.
- Never connect the unit to an electrical outlet using an extension cord. If an outlet is not available, one should be installed by a qualified electrician.
- Do not operate the unit unless it has been fully installed following the guidance provided within this manual.
- Never operate this appliance if the cord or plug is damaged. Ensure the power cord is not stretched or exposed to sharp objects/edges.
- A damaged supply cord should be replaced by the manufacturer or a qualified electrician in order to avoid a hazard.
- Any service other than regular cleaning or filter replacement should be performed by an authorised service representative. Failure to comply could result in a voided warranty.
- Do not use the appliance for any purpose other than its intended use.
- Avoid restarting the air conditioner unless 3 minutes have passed since being turned off. This prevents damage to the compressor.
- Never use the mains plug as a switch to start and turn off the air conditioner. Use the provided ON/OFF button located on the control panel.
- The appliance should not be installed in laundry or wet rooms.
- The appliance must be installed in a room without sources of ignition (for example: open

SAFETY WARNING

flames, an operating gas appliance or an operating electric heater).

- The unit must be installed on a solid vertical wall by a competent person. The electricity supply must only be connected after installation is complete.
- R290 refrigerant gas complies with European environmental directives.
- R290 has a low GWP (Global Warming Potential) of 3.
- These air conditioners contains about 290 g of R290 refrigerant gas.
- Do not install or store in an unventilated space with an area smaller than 15m² per unit. The room must be such as to prevent stagnation of possible leaks of refrigerant gas as there could be a danger of fire or explosion hazard should the refrigerant come into contact with electric heaters, stoves or other sources of ignition.
- If the appliance is installed, used or stored in an unventilated room, the room must be such as to prevent stagnation of possible leaks of refrigerant gas as there could be a danger of fire or explosion should the refrigerant come into contact with electric heaters, stoves or other sources of ignition.
- Refrigerant gas may be odourless.
- Do not use the product and contact the retailer for advice, if damage has occurred to the unit which may have compromised the refrigerant system.
- Any repairs or maintenance must only be carried out on the unit by a suitably qualified engineer. Before opening and servicing the unit the authorized engineer must be in possession of a copy of the manufacturer's service manual and must follow the safety information contained within it to ensure all hazards are minimized.
- The refrigerant system should not be perforated or punctured.

Energy Saving and Unit Safety Protection Tips

- Do not cover or restrict the airflow from the outlet or inlet grills. A minimum distance of 50cm is advised.
- Keep the filters clean. Under normal conditions, filters should only need cleaning once every three weeks (approximately). Since the filters remove airborne particles, more frequent cleaning maybe necessary, depending on the air quality.
- For the initial start-up set the fan speed to maximum and the thermostat to 4-5 degrees lower than the current temperature. After, set the fan switch to low and set the thermostat to your desired setting.
- To protect the unit, we recommend not using the cool mode when the ambient temperature is higher than 35°C.

NOTE: Some pictures and information may vary from the final product. This is due to continual product improvement.

PRODUCT OVERVIEW

PRODUCT DIAGRAM

FRONT



FEATURES

- Simple operation
- · High and low installation options for added versatility
- Self-evaporative function with energy saving technology
- · Sleek design that seamlessly fits into any style home
- Bright LED screen Indicates temperature and current mode
- On/Off timer function Allows you to choose when the unit operates
- WIFI App control providing additional functionality
- Three fan speeds
- PTC heater ideal for lower temperatures
- Four modes to suit your every need including: Cooling/Heating/Fan/Dry.
- Silent running option, perfect for a restful night sleep

WHATS INCLUDED



WIRED CONTROLLER AVAILABLE SEPERATELY FROM THE RETAILER UNDER REFERENCE: IQOOLSMART12HP-WiredCtrl

INSTALLATION TOOLS REQUIRED



BEFORE STARTING INSTALLATION, PLEASE ENSURE YOU HAVE ALL SUITABLE EQUIPMENT AVAILABLE AND UNDERSTAND THE STEPS INVOLVED IN INSTALLATION. IF IN ANY DOUBT, PROFESSIONAL ADVICE SHOULD BE SOUGHT.

THE INSTALLER MUST ENSURE THAT THE PLANNED POSITION OF THE AIR CONDITIONER IS SUITABLE, AND THAT THERE ARE NO CABLES, PIPES OR OTHER OBSTRUCTIONS, WHICH WOULD PRESENT A DANGER AND/OR PREVENT COMPLETION OF INSTALLATION.

INSTALLATION



This unit must be installed on an external wall, as it vents directly out of its rear.

Only install the unit on a flat, solid and reliable wall. Ensure that there are no cables, pipes, steel bars or other obstructions behind the wall.

Leave at least 10 cm of space to the left and right of the machine. At least 20cm of space must be left above the unit to help the air flow smoothly. A minimum distance of 50cm is advised from the front of the unit.





The hole for the drainage pipe must be drilled using a 25mm Drill bit. Ensure the hole is at a downward angle (min 5 degrees) so that the water will drain correctly. It is recommended to insulate any parts of the drain pipe which is accessible to prevent the build up of ice when running at low temperatures.

Use a 180 or 182mm core drill to drill the two holes for the units ventillation, ensuring that both the holes are aligned with the template.

Paste the supplied installation template paper in position on the wall, ensuring that the reference line is level using a spirit level.

Use the template to mark the position of the screws for the hanging rail, using a spirit level to ensure it is straight and level.

Drill the marked holes using a suitable 8mm drill bit and insert wall plugs. Line the hanging rail with the holes, and fix the rail into position using the supplied screws.

Ensure that the hanging rail is securely fastened onto the wall, and that there is no risk of the unit tipping or falling.



Roll the plastic vent sheets into a tube and feed them from the inside into the holes previously made. Ensure the tubes sit flush to the interior wall.





Go outside and trim off the excess vent tube using a sharp knife, keeping the edge as neat as possible.

Insert the indoor fixing ring from the vent cover onto the indoor side of the air vent. Then fold the external vent cover in half. Attach the chains to each side of the vent cover, before sliding the cover outside through the vent hole.







Expand the external cover, before tightly fixing the chains by hooking onto the indoor fixing ring. This will hold the external cover firmly in position. Repeat for the second vent.

Note: The external cover should be positioned so that the slats within it are horizontal, with the exhaust aimed downwards.

Once the chains are fitted and secure, any excess chain should be removed by cutting the chain.

We would also advise running a bead of exterior caulk or similar around the external vent to help prevent water ingress.





Lift the unit onto the wall, align the hanging holes with the hooks on the hanging rail and gently rest the unit into place. At the same time, slide the drain pipe through the drainage hole. If the wireless controller (Available separately) has been purchased, it should then be installed, and connected.

NOTE: The end of the external water pipe must be placed in an open space or drain. Avoid damage or constriction to the drainage pipe to ensure the unit drains.

Place the bracket in position on the under side of the unit and mark the position of the screw hole on the wall.

Remove the bracket and drill a hole using a 8mm drill bit before inserting a wall plug.

Fix the bracket into position on the underside of the unit using the 2 small screws. Then attach the bracket to the wall using a screw through the wall plug previously inserted.



ATTACHING THE BOTTOM COVER

Note: Attachment of the bottom cover is optional. The bottom cover is designed to give the bottom of the unit a more attractive appearance when the unit is mounted at a height and the underside is visible.

Following installation, use a screwdriver to remove the 4 rubber feet and the water tank braket from the underside of the appliance.





Place the bottom cover plate in position on the underside of the appliance, with the lips pointing up (small lip at the rear of the unit)



Attach the bottom plate using the screws removed from the feet. When fitting the bottom plate, all 4 screws should be fitted loosely, so the position of the plate can be adjusted before fully securing into position.

OPERATION CONTROL PANEL



REMOTE CONTROL

The air conditioner can be controlled with the remote control. Two AAA-batteries are required.

NOTE: Further details of the functions can be found on the following page.

POWER	Press the POWER button to turn the machine on or off.
MODE	Press the MODE button to switch between cooling, heating, fan and dry modes.
FAN	Press the FAN button to change between high, medium and low fan speeds
LED	Press to turn the LED display on the unit on and off.
	Press the UP button to increase the desired temperature or timer duration
▼	Press the DOWN button to decrease the desired temperature or timer duration
РТС	Press to turn the PTC Heater on and off.
SILENT	Press to activate SILENT mode. In silent mode the fan will run at low speed to minimise the operating noise of the unit.
SWING	Press to turn the swing function on and off (Can only be activated from the remote)
TIMER	Press the TIMER button to set the timer.



FUNCTIONS

POWER	Press "POWER" to turn the unit On or Off				
	Press to char currently sel	nge between the 4 different modes. The display will show the symbol for the mode ected.			
	COOLING	Cooling mode defaults to 22°C and will cool the air while sending warm air outside. The desired temperature can be adjusted using the increase and decrease button between 16°C and 30°C. The fan speed can also be adjusted using the speed button.			
	DRY	Dry mode will extract moisture from the air, which will be drained outside using the installed drain pipe. The fan speed cannot be adjusted in dry mode.			
MODE	FAN	In fan mode the appliance will recirculate the air within the room, and will not cool or dehumidify. The fan speed can be adjusted using the Speed button.			
	HEATING	Heating mode defaults to 24°C and will heat the air while sending cool air outside. The desired temperature can be adjusted using the increase and decrease button between 16°C and 30°C. The fan speed can also be adjusted using the speed button.			
	SILENT	Silent mode can only be activated from the app or control panel by pressing the timer and up buttons at the same time. It will only operate in cooling mode. The fan speed will change to low, and the desired room temperature will increase by 1°C after 1 hour, and a second 1°C after 2 hours, reducing the amount of time the compressor operates.			
FAN SPEED	attil	Press to change the fan speed between Low, Medium and High. The fan speed cannot be adjusted in Dry or Sleep modes.			
	set period of	itioner contains a 24 hour timer, which can be used to either set a delayed start, or a operation. The timers cannot be combined, although the app can be used to iods of operation.			
	SHUTDOWN TIMER : While the unit is running press the timer button, the display will flash "0" 5 times. After the 5 th flash, use the up and down buttons to adjust the duration in 1 hout increments between 1 to 24 hours. When the timer has elapsed, the unit will shutdown automatically.				
TIMER	DELAYED START TIMER: With the unit in standby, press the timer button, the display will flash "0" 5 times. After the 5 th flash, use the up and down buttons to adjust the duration in 1 hout increments between 1 and 24 hours. After the timer has elapsed, the unit will start up in the same mode with the same settings as when it was turned off.				
	Used within cooling and heating modes to adjust the desired room temperature. Also used while setting the timer to adjust the duration.				
INCREASE AND DECREASE		Id the INCREASE and DECREASE buttons at the same time to change the display on banel between farenheit and Celcius. Note the display on the remote cannot be			
SWING MODE	After machin by pressing t	te turns on, press the "SWING" button, louver will swing continuously up and down; he button again the movement will stop and the louver remain in that position. Swing ally be adjusted from the remote, and will initially be turned on by default.			
COMPRESSOR PROTECTION	There is a 3 r	ninutes delay on power on. In order to protect the life of the compressor and mponents please do not switch on the unit for at least 5 minutes after you turned the			

PTC HEATER

This airconditioner contains an intelligent 1KW PTC heater, which is especially useful in low temperature applications. It provides both a boost to the heat output of the appliance, as well as increasing the performance of the heatpump in low temperature conditions, by warming the cold coils, preventing the unit from entering defrost mode. This helps the room to reach the desired temperature as quickly as possible.

As well as warming the inside of the unit, the PTC heater will also provide extra heat to warm the room, which is expelled out of the unit and into the room

The PTC function can only be acticated using the remote control and once activated, the PTC HEAT symbol will display on both the appliance and the remote. In order to ensure efficient operation the PTC heating element will only activate when the following conditions are met:

- 1) The unit is in heating mode.
- 2) The outdoor temperature is below 25°C.
- 3) The desired room temperature at least 5°C higher than the current room temperature.
- 4) The internal temperature of the evaporator coils within the appliance is below 48°C.
- 5) The compressor is running to increase the room temperature

If any of the above conditions are met while the PTC heater is operating, the PTC heater will turn off. The PTC function can also be manually turned off by pressing the PTC button on the remote.

Please note: As the electrical heating used in the PTC heater is less efficient than the heatpump, this feature is not activated when the unit is turned on, and must be reactivated if required each time the appliance is started.

WIFI SETUP

BEFORE YOU START

- Ensure your router provides a standard 2.4ghz connection.
- If your router is dual band ensure that both networks have different network names (SSID). The provider of your router / Internet service provider will be able to provide advice specific to your router.
- Place the air conditioner as close as possible to the router during setup.
- Once the app has been installed on your phone, turn off the data connection, and ensure your phone is connected to your router via wifi.

DOWNLOAD THE APP TO YOUR PHONE

Download the "TUYA SMART" app, from your chosen app store, using the QR codes below, or by searching for the app in your chosen store.





Android

IOS

CONNECTION METHODS AVAILABLE FOR SETUP

The air conditioner has two different setup modes, Quick Connection and AP (Access Point). The quick connection is a quick and simple way to set the unit up. The AP connection uses a direct local wifi connection between your phone and the air conditioner to upload the network details.

Before starting the setup, with the air conditioner plugged in, but turned off, press and hold the Fan Speed button on the air conditioner for 5 seconds (until you hear a bleep) to enter the wifi connection mode. Please note the WIFI mode cannot be adjusted from the remote.

Please ensure your device is in the correct WIFI connection mode for the connection type you are attempting, the flashing of the WIFI light on your air conditioner will indicate this.

Connection Type	Frequency of Flashes
Quick Connection	Flashes twice per second
AP (Access Point)	Flashes once per three seconds

CHANGING BETWEEN CONNECTION TYPES

To change the unit between the two WIFI connection modes, hold the Fan Speed button on the air conditioner for 3 seconds.

REGISTER THE APP

 Press on the register button at the bottom of the screen. 	2. Read the Privacy policy and press the Agree Button.	3. Enter your email address or phone number and press continue to register.
	← Privacy Policy	← Register
	Privacy Policy of Tuya Smart Platform	United Kingdom +44
tuya	Update date: 2018.4 Come into force date: 2018.5	Mobile number/Email
Register Log in	So you have purchased our TuyaSmart device hardware and are starting to use the TuyaSmart device software and all its functionalities! Any information you share with us (e.g. for creating a Tuya Account) will help us to provide you with services related to TuyaSmart device and to improve them to make them even better. We explain here our ways of collecting and using information, and how we protect your privacy. In this privacy policy, "personal data" means infor that can be used to identify an indi- either from that information alone, that information and other inform	Continue no hi so $q^{1}w^{2}e^{3}r^{4}t^{5}y^{6}u^{7}i^{8}o^{9}p^{6}$ a s d f g h j k l $4z$ x c v b n m \propto ?123 ,
 A verification code will be sent by the method selected in step 3. Enter the code into the app. 	5. Type in the password you would like to create. This needs to be 6-20 characters, with letters and numbers.	 The app is now registered. It will automatically log you in following registration.
÷	~	
Verification Code	Set Password Password must contain 6-20 letters and numbers Done	
	no hi so	Enjoy your smart life
1 2 3 -	qwertyuiop 22dfabikl	Add Home
4 5 6 ,	asdfghjkl ♠zxcvbnm ⊠	
7 8 9 🖾		Log out
. 0 🗸	,	

SETTING UP YOUR HOME WITHIN THE APP

TUYA is designed so it can work with a large number of compatible smart devices within your home. It can also be set up to work with multiple devices within different houses. As such during the setup process, the app requires that different areas are created and named to allow easy management of all your devices. When new devices are added, they are assigned to one of the rooms you have created.

CREATING ROOMS

1. Press on the AD button.	DD HOME	-	/pe in a na ome,	ame for your	÷	Add Home	Done
		to hc Y(select the ome. (See OUR LOC	e location button location of your SETTING ATION below)	Name Location	Enter your home name Set geographic location	>
. 7			ew rooms / pressing	can be added	Smart device	es in:	
		Ai th Ai	NOTHER e bottom. NOTHER	ROOM option at (See ADD ROOM below) ooms that are	Living Roo Bedroom	m	0
		nc	ot required	on the app.	Second Be	droom	0
Enjoy	art life		ress DONI orner.	E in the top right	Dining Roc	om	0
Add Home	e				Kitchen		0
					Study Roo	m	0
Log out					Add anoth	er room	
SETTING YOUR L	OCATION		16	ADD ANOTHER	ROOM		
SETTING YOUR L		luger y	CONFIRM	ADD ANOTHER	ROOM	Add a Room	Done
		Poundstretc		Type in the name of the room, and			Done
Use your finger to move the orange HOME symbol. When the symbol is in the approximate location of your home, press the	CANCEL Destation Rd	tune Way		Type in the name of the	← Room N Recomme	ame nded Room Bedroom d Bedroom Dining Room n Study Room Po	Done
Use your finger to move the orange HOME symbol. When the symbol is in the approximate location of your home, press the	CANCEL Derinion Ro Buddersf Appliances Direct	tune Way	ther DC	Type in the name of the room, and press Done in the top right	← Room N Living Secon Kitche Balcon	ame nded Room Bedroom d Bedroom Dining Room n Study Room Po) rch akroom
Use your finger to move the orange HOME symbol. When the symbol is in the approximate location of your home, press the confirm button in the top right	CANCEL Derinion Ro Buddersf Appliances Direct	tune Way	ther DC	Type in the name of the room, and press Done in the top right	← Room N Living Secon Kitche Balcon	ame nded Room Bedroom d Bedroom Dining Room n Study Room Po n Study Room Po n Study Room Close no hi sub e r t y u i s d f g h j	rch akroom ° ° ° ° ° ° ° °

CONNECTING USING QUICK CONNECTION

Before initiating the connection, make sure the unit is in standby mode, with the WIFI light flashing twice per second. If not follow the instructions for changing the connection mode. Also ensure your phone is connected to the WIFI network. (We advise turning mobile data off during setup)



CONNECTING USING AP MODE (ALTERNATIVE METHOD)

Before initiating the connection, make sure the unit is in standby mode, with the WIFI light flashing once per second. If not follow the instructions for changing the WIFI connection mode. Also ensure your phone is connected to the WIFI network. (We advise turning mobile data off during setup)



your phone has reconnected to your WIFI router.

CONTROLLING YOUR DEVICE THROUGH THE APP

THE HOME SCREEN



Add Device: Add a device

Each device has its own entry on the home screen to allow the user to either quickly turn the unit on or off, or to enter the device screen to make other changes.

DEVICE SCREEN

All Device	s -Light	-Plug	-Camera	¢	
	Electriq Turned on		(و	
Name of Air Conditioner: Press to enter the Device Screen					ON / OFF Button: Use to quickly turn the unit on or off.

DEVICE SCREEN

The device screen is the main control screen for the air conditioner, providing access to the controls to amend the functions and settings



*Due to continuous development of the app, the layout and available features may be subject to change.

SMART SCENES

Smart Scenes is a powerful tool providing the option to customise the operation of the air conditioner based both on conditions within the room and outside influences. This gives the user the option of specifying much more intelligent actions. These are split into two catagories Scene and Automation.

SCENE

Scene allows for a one touch button to be added to the Home screen. The button can be used to change a number of settings in one go, and can change all the settings within the unit. A number of scenes can easily be setup, allowing the user to easily change between a number of preset configurations.

Below is an example of how to set up a scene:



AUTOMATION

Automation allows an automatic action to be set up for the device. This can be triggered by the Time, indoor temperature, humidity of the room, weather conditions, and a range of other influences.



PROFILE	Settings
Tap to set your name	>
% Scenes	>
∞ Device Sharing	>
☑ Message Center	>
☑ Integration	>
♡ Experience Center	>
🗄 Scan QR Code	>
⑦ FAQ	>
···· Feedback	>
Devices Scenes F	Profile

PROFILE TAB

The profile tab gives you the option to edit both your detail, and use the added features of the unit.

CHANGING THE NAME OF YOUR DEVICE

When in any of the device screens further settings for the device can be accessed, by pressing on the three dots in the top right hand corner. The top option within this allows you to change the name of the device to something relevant to the use of the product, such as "Living Room Air Conditioner". Within the menu, you also have the option of setting up a pattern lock or change your password.

DEVICE SHARING

This allows you to share access to the controls of your air conditioner with friends and family.

INTEGRATION

This allows the unit to be integrated with your favourite home automation hardware such as Google Home and the Amazon Echo.

CONNECTION TROUBLESHOOTING

- 1. Check whether the device is powered on and is in the correct WIFI connection mode, if not please refer to the CHANGING BETWEEN CONNECTION MODES section on page 12.
- 2. Ensure the WIFI password has been entered into the app correctly (Case sensitive)
- 3. Check that the phone is connected to the WIFI you are connecting the device to.
- 4. Ensure the network you are connecting it to is 2.4Ghz (5Ghz WIFI networks are not supported), and that there is a strong WIFI signal to the item.
- 5. If your router is dual band, ensure that the 2.4ghz network has a different network name (SSID). Further advice on changing router settings will be available from your Internet service provider / Router manufacturer.
- 6. Check the settings on the router. Encryption should be WPA2-PSK and authorisation type should be set to AES
- 7. Try using the alternative connection method. i.e. If connection is failing when attempting to connect through CF mode, try AP mode.

TROUBLESHOOTING

Do not repair or disassemble the air conditioning. Unqualified repair will invalidate the warranty and may lead to failure, causing injuries and property damage. Only use it as directed in this user manual and only perform operations advised here.

Problem	Reasons	Solutions		
	There is no electricity.	Check the unit is plugged in, and the socket is working normally.		
	The ambient temperature is too low or too high	Only use to use the machine with a room temperature between 7 and 35°C		
The air conditioner does not work.	In cooling mode, the room temperature is lower than the desired temperature; in heating mode, the room temperature is higher than the desired temperature.	Adjust the desired room temperaure		
	In dehumidification (dry) mode, the ambient temperature is low.	Ensure that the room temperature is above 17°C for dry mode.		
	There is direct sunlight.	Use curtains to reduce heat from the sun		
The cooling or heating	Doors or windows are open; there are a lot of people; or in cooling mode, there are other sources of heat (e.g. fridges)	Close doors and windows; increase air conditioning power		
effect is poor	The filters screen is dirty.	Clean or replace the filter screen.		
	The air inlet or outlet is blocked.	Clear obstructions; make sure the unit is installed as per the instructions		
The air conditioner is	The unit is not straight	Use a spirit level to check the unit is horizontal, if not remove from the wall and straighen		
leaking	The drain pipe is blocked	Check the drain pipe to ensure it is not blocked or constricted.		
Compressor does not work. Overheat protection operational		Wait for 3 minutes until the temperature is lowered, and then restart the machine.		
	The distance between the machine and the remote control is too far.	Let the remote control get close to the air – conditioner, and make sure that the remote		
The remote control does not work.	The remote control is not aligned with the direction of the remote-control receiver.	control directly faces to the direction of the remote-control receiver.		
	Batteries are dead.	Replace batteries.		

If problems not listed in the table occur or recommended solutions do not work, please contact the service centre.

ERROR CODES

Fault Code	Fault Description	Fault Code	Fault Description
F1	Compressor IPM error	FE	EE error (condenser circuit)
F2	PFC/IPM error	PA	Return air sensor temperature abnormal protection
F3	Compressor start error	P1	Over-heat protection on top of compressor
F4	Compressor running out of step	PE	Abnormal refrigerant circulation
F5	Location detection loop failure	РН	Exhaust temperature protection
FA	Phase current overcurrent protection	PC	Coil tube overload protection (condenser circuit)
P2	Dc bus voltage Undervoltage protection	E3	DC fan Feedback failure (evaporator circuit)
E4	Communication error (evaporator circuit and condenser circuit)	P6	Coil tube overload protection (evaporator circuit)
F6	PCB communication error	P7	Defrost protection on coil tube (evaporator circuit)
Р3	AC Input voltage protection	E2	Sensor error on indoor coil tube
P4	AC over-current protection	E1	Temperature sensor error (evaporator circuit)
Р5	AC undervoltage protection	P8	Zero-crossing fault detection (evaporator circuit)
F7	Coil sensor error(condenser circuit)	EE	EE error (evaporator circuit)
F8	Sensor on suction pipe error	E5	Water-splash motor error
EO	Sensor on discharge pipe error	E8	Fan feedback fault
E6	Temperature sensor error (condenser circuit)	FL	Water-full protection
E7	Fan motor error (condenser circuit)		

TECHNICAL DATA

MODEL	IQOOL-SMART12HP-V2	IQOOL-SMART15HP-V2	
Capacity Cooling/Heating	2.93 / 2.63KW 3.5 / 2.93K		
Rated Input Cooling / Heating	1120W / 730 W 1350W / 815		
Running Current Cooling/Heating	5.0A / 3.5A 6.0A / 4.0A		
EER rate	2.6	i	
Compressor	Rotary, 290g	g R290 gas	
Noise	58dB (A)	60dB (A)	
Thermostat	16 - 3	0°C	
PTC Power	800W		
Permitted Excessive Operating Pressure	0.8/2.8	MPa	
Maximum Allowable Pressure	1.3/3.8MPa		
Power Supply	220-240V / 50Hz		
Net Weight	38Kg	39Kg	
Dimension(L*D*H)	1000 x 20	5 x 585	



UK SUPPORT electriQ UK SUPPORT

www.electriQ.co.uk/support

Please, for your own convenience, make these simple checks before calling the service line.

- 1. Has the unit been standing upright for at least 2 hours?
- 2. Is the unit plugged into the mains?
- 3. Is the fuse OK?
- 4. Switch the unit off and wait three minutes to see if the issue is resolved. Restart the unit.
- 5. Was the troubleshooting guide followed?

If the unit still fails to operate call: 0330 390 3061 or complete the online form

Office hours: 9AM - 5PM Monday to Friday

Unit J6, Lowfields Business Park, Lowfields Way, Elland West Yorkshire, HX5 9DA

DECLARATION OF CONFORMITY

Hereby, electriQ declares that this Portable air conditioner is in compliance with Directive 2014/53/EU. The full text of the EU declaration of conformity is available at the following internet address:

https://www.electriQ.co.uk/content/declaration-of-conformity

Disposal: Do not dispose this product as unsorted municipal waste. Collection of such waste must be handled separately as special treatment is necessary.



Recycling facilities are now available for all customers at which you can deposit your old electrical products. Customers will be able to take any old electrical equipment to participating civic amenity sites run by their local councils. Please remember that this equipment will be further handled during the recycling process, so please be considerate when depositing your equipment. Please contact the local council for details of your local household waste recycling centres.