

PAC EX130

DE'LONGHI COMFORT

AIR-TO-AIR PORTABLE CONDITIONERS

ECOREAL FEEL

- **Maximum cooling capacity** 13.000 Btu/h* - 3,3 kW
- **Low Energy Consumption** Class A
- **Eco Real Feel Technology savings***** Up to 30% Energy
- **Eco-friendly gas** R290
- **Silent**
- **Frontal display** Easy to read
- Fan function
- Dehumidifying function
- LED control panel with Comfort Light Indicator
- Exclusive condensate recirculation system
- 3 fan speed to select the maximum power or the minimum noise
- Soft touch control panel
- Remote control
- **24 h** electronic timer and thermostat
- Handles and castors for easy transportation
- Eco-Design



2,7 kW



ECO REAL FEEL



EFFICIENCY	SILENT TECHNOLOGY	700 TIMES ECO-FRIENDLY	ECO REAL FEEL TECHNOLOGY	COMFORT LIGHT INDICATOR / WIDE DISPLAY
Perfect match of most advanced technology and low consumption, Pinguino PAC EX130 ECO REALFEEL is A class of Energy Efficiency.	The silence of power, up to 50% more silent* (Tested in our labs by comparing the max fan speed vs min fan speed)	Pinguino PAC EX130 Ecoreal Feel uses the refrigerant gas R290 , which is up to 696 times more environmentally friendly than traditional gases****	Comfort is the result of correct matching between temperature and humidity. ECO REAL FEEL tracks and acts on both to automatically reach and maintain your desired comfort, at the same time saving up to 30% *** on energy consumption.	Immediate understanding of comfort level thanks to the CLI Comfort Light Indicator: orange "seeking for comfort", green "good comfort level" Blu "perfect comfort". Increased easy of use thanks to the frontal display.

TECHNICAL DATA

Maximum cooling capacity	BTU/h* – Kw**	13.000 – 3,3
Energy Efficiency Ratio (EER)	(W/W)	2,6
For rooms up to	m ³	120
Refrigerant gas		R290
Energy Efficiency Class		A
Rated voltage – frequency	V~Hz	220-240~50
Input power**	W	1300
Standby consumption	W	0,8
Maximum sound power level	dB(A)	65
Noise pressure level (min-max)	dB(A)	47-50
Air flow(min-med-max)	m ³ /h	235-270-310
Max dehumidifying (dehum. mode)	l/24h	36
Dimensions (hxlxp)	mm	805x445x390
Weight	Kg	32

* 35°C/80% R.H.

** 35°C/40% R.H. (EN14511)

***Internal test, initial condition 30° C and 40%RH

****696 times compared to the impact of Global Warming of R410 - F-Gas Reg. 517/2014.

***** Tested in our laboratory by comparing the maximum sound level using max. fan speed vs sound level with min. fan speed



Better Everyday