

TECHNICAL SPECIFICATIONS		
Model	eIQ-9WMINVB	
Rated volt and frequency	1-220-240/50	
Mode	Cooling	Heating
Rated capacity (W)	2500 (1600~ 3100)	2500 (1500~ 3200)
Cooling power input (W)	670 (390~1110)	660 (320~940)
Heating current input (A)	3 (1.9~ 4.8)	2.9 (1.6~ 4.1)
SEER/SCOP(W/W)	6.1/ A++	4.0/ A+
Nominal load (kW)	2.5	2.5
Balance point temperatureheating (°C)	/	-7
Min.outdoor operating temperature (°C)	/	-10
Thermostat-off mode (W)	30	
Standby mode (W)	0.5	
Off mode (W)	0	
Annual consumption (KW)	143	875
Copper Pipe Type length	5m	
Liquid side/Gas side (mm/inch)	6.00(1/4)+9.52(3/8)	
Max.refrigerant pipe length	15m	
Max.elevation	5m	
Interconnecting Cable	3C+E	
Fuse Rating	13A	
Moisture Removal (L/h)	0.95	
INDOOR UNIT	Air Flow (m3/h)	550
	Dimension (L*W*H) (mm)	780x276x202
	Packaging (L*W*H) (mm)	960x367x305
	Net/Gross weight (Kg)	10/12
	Noise - Sound pressure level (dB/A)	30~42
	Noise - Sound power level (dB/A)	40~52
OUTDOOR UNIT	Dimension (L*W*H) (mm)	715x235x540
	Packaging (L*W*H) (mm)	851x335x600
	Net/Gross weight (Kg)	27/29
	Noise - Sound pressure level (dB/A)	53
	Noise - Sound power level (dB/A)	63

	Refrigerant type/weight	R410A/700g
	Defrost mode	Automatic