

Model		eiq-SSRFC48k
Power supply		V,Hz,Ph
Max. input consumption		W
Max. input current		A
Compressor	Model	ATQ420D1UMU
	Type	ROTARY
	Brand	GMCC
	Capacity	Btu/h
	Input	W
	Rated current(RLA)	A
	Refrigerant oil	ml
Outdoor fan motor	Model	ZKFN-85-8-22+ZKFN-85-8-22-2
	Old Model	- -
	Qty	1+1
	Input	W
	Capacitor	μF
	Speed(Hi)	r/min
Outdoor coil	Number of rows	1.6
	Tube pitch(a)* row pitch(b)	mm
	Fin spacing	mm
	Fin type	Hydrophilic aluminium
	Tube outside dia.and type	mm
	Coil length * height * width	mm
	Number of circuits	8
Outdoor air flow		m3/h
Outdoor sound pressure level		dB(A)
Outdoor sound power level		dB(A)
Throttle type		Capillary +EXV
Outdoor unit	Dimension(WxDxH)	mm
	Packing(WxDxH)	mm
	Net/Gross weight	kg
Refrigerant	Type	R410A
	GWP	2088
	Charged quantity	Kg
Design pressure		MPa
Refrigerant piping	Liquid side/ Gas side	mm(inch)
	Max. pipe length	m
	Max. difference in level	m
Ambient temperature	Cooling	°C
	Heating	°C